

T *SERIES*
MAJOR

SN 5800 V



AC TRACTORS

The SN 5800 V Major is an isodiametric compact tractor with articulated frame from the TMajor Series that offers a perfect blend of ergonomics, reliability and versatility combined with a very narrow track width (just 98 cm!).

Ideally suited to use in narrow crop rows, also on steep gradients, with a very small turning radius, wrap-around mudguards and streamlined side panels, all designed for easy access to even the tightest spaces.



ANTONIOCARRARO.COM



N°1 SPECIAL TRACTORS

TECHNICAL DATA:

SN 5800 V

Frame ACTIO™ integral oscillating frame • Articulated • 4 equal-size wheels • Rear final drives

Engine type Supercharged diesel with common rail direct injection
 Emissions Standard: **Stage 5**
 N° Cylinders: 4 - 16 Valves
 Rated rpm: 2600
 Tank capacity (litres): 38.5

Power kW/CV (97/68/CE): 37.9/ 51,5
 Max torque (Nm/rev): 168,2 Nm/1690

Transmission 24 speed synchronised gearbox: 12 FWD + 12 REV with shuttle

PTO Independent, mechanical control, standard 540 rpm and synchronised groundspeed

Shaft 1 3/8" splined

Rear linkage Rear hydraulic lift with 3-point linkage
 Lifting capacity (kg): 1700
 Oscillating lift arms and lateral stabilizer bars, Cat. 1;
 Category "C" adjustable rear tow hook

Steering Hydraulic 2 pistons

Brakes Service brakes: rear oil-immersed disc brakes with hydraulic control;
 Emergency and parking brake: transmission brake band

Standard Features

- Mechanically-controlled front and hydraulically-controlled rear differential locks
- Adjustable driving seat with suspension
- Safety belts
- Adjustable rear tow hook
- Front tow hook
- Folding roll bar
- Adjustable wheel discs
- Horn
- Lights and direction indicators
- 3- and 7-pole electrical outlet sockets
- Central control panel
- Safe start switch
- Digital speedometer
- Battery disconnect
- Provision for flashing light attachment

Optional

- Hydraulic lift with position and draft control
- 540 and 1000 rpm PTO
- Directable rear LED worklight
- 4 types of hydraulic system with single- and double-acting remote valves (5 rear quick couplers)
- Wheel ballasts
- Lift arms with sliding quick hitches
- Tilt-adjustable steering column
- Pneumatic seat suspension
- Mudguard extensions

Dimensions with 250/80 - 18 tyres

