





TRX: MADE TO MEASURE

TRX is a multi-purpose specialised tractor ideal for open field or row crop applications, in orchards and vineyards, on level ground or slopes. The TRX is an isodiametric, made-to-measure specialised tractor, offering outstanding manoeuvrability with a tight turning radius.

Thanks to the sparkling performance of the engine and constant grip ensured by the overhung engine and four-wheel drive, the TRX is stable in all situations. The TRX's extraordinary versatility is a result of the reversible driving position: this feature enables a whole new approach to working procedures, allowing the use of a wide range of implements for ploughing, spraying, harvesting, towing, green keeping, forestry and construction site work. The reversible driving position and ergonomic control layout simplify the task of the operator, thereby reducing fatigue and stress.







Chassis: "ACTIO[™] – Full chassis with oscillation • Reversibility RGS[™] • Steering wheels • 4 equal wheel drive • Front and rear final drive

Engine mod. 7800: Stage 5 and EPA TIER 4 - 4 Cylinders - 16 Valves Common rail - Power 51,7 kW / 70,3 HP - 2500 rpm -3319 CC

Transmission: Synchronized 32 speed gear box: 16 forward and 16 reverse with synchronized inverter

PTO: Rear, independent and synchronized at 540/540E rpm with progressive electrohydraulic engagement

Rear hydraulic lift: with 3 point hitch Operating Pressure 160 bar - Capacity 2150 Kg


Brakes: Standard: hydraulic front and rear disk brakes in oil bath, rear steering brakes - Independent emergency and parking brake: band type on transmission

Weight Kg: With roll bar 2080+2180 - With cabine 2220+2320





DIMENSIONS: tyres 250/80-18



**Height calculated with the operator of average height sitting (cm 175)









Standard equipment

• RGS[™] Reversible driving position • Differential locking on rear axle only or both axles with electro-hydraulic control • Lift arms with Cat. 1-2 fixed ball ends • Sprung adjustable seat with safety belt • Folding front roll bar with easy operation • Adjustable wheel discs • Rear auxiliary hydraulic system with 3 control levers • Height-adjustable rear tow hook • Multifunction digital console • Accelerator pedal suspend on turret • Battery • Battery disconnector • Electrical outlet socket • Safe start system on shuttle control, on PTO and on seat

Optional

• StarLight cab with air conditioning and roof hatch on Silent Block mountings; (on request) active carbon filters • EasyStar 6-pillar safety frame, on Silent Block mountings • Hydraulic system with "JPM" proportional joystick • Power lift with draft and position control and 3-point linkage

ANTONIO CARRARO SPA info@antoniocarraro.it antoniocarraro.com